SAFETY DATA SHEET

DELO-DUOPOX® AD840 Component A

DELO

Section 1. Identification

GHS product identifier

: DELO-DUOPOX® AD840 Component A

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use of the substance/mixture: Adhesive. Process categories [PROC]: PROC01: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC02: Use in closed, continuous process with occasional controlled exposure. PROC03: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition. PROC04: Chemical production where opportunity for exposure arises. PROC05: Mixing or blending in batch processes. PROC09: Transfer of substance or mixture into small containers (dedicated filling line, including weighing). PROC10: Roller application or brushing. Environmental release categories [ERC]: ERC02: Formulation into mixture. ERC05: Use at industrial site leading to inclusion into/onto article. Product categories [PC]: PC01: Adhesives, sealants. Sector of uses [SU]: SU03: Industrial uses. SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys). SU16: Manufacture of computer, electronic and optical products, electrical equipment. SU17: General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment. SU22: Professional uses.

*: Mixture.

Manufacturer	: DELO Industrie Klebstoffe GmbH & Co. KGaA DELO-Allee 1 86949 Windach Germany
Information contact	: DELO Industrial Adhesives L.L.C. 144 North Road, Suite 2650 Sudbury, MA 01776 USA
e-mail address of person responsible for this SDS	: sds@DELO.de
<u>In case of emergency</u>	 National advisory body/Poison Center In case of emergency [Transport]: in USA: GlobalChem24: 001 215 207 0061 in Europe: GlobalChem24: +44 (0) 1235 239 670 24-hour telephone and/or website

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	: SKIN IRRITATION - Category 2
substance or mixture	EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Precautionary statements	
Prevention	: Wear protective gloves: 1 - 4 hours (breakthrough time): Recommended: Viton® fluor rubber / Short term exposure < 15 min Nitrile gloves. Wear eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture		
Hazardous ingredients :		
Ingredient name	%	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	25 - 75 10 - 25	25068-38-6 9003-36-5
Phenol, polymer with formaldehyde, glycidyl ether titanium dioxide, nanoparticle	10 - 25 < 1	28064-14-4 13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures		
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. 	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	

Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/symp	<u>itoms</u>	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Storage temperature: Observe technical data sheet/instructions for use. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits
reaction product: bisphenol average molecular weight ≤	-A-(epichlorhydrin); epoxy resin (number ; 700)	None.
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol		None.
Phenol, polymer with formaldehyde, glycidyl ether		None.
titanium dioxide		None.
ppropriate engineering ontrols	: Good general ventilation should be contaminants.	sufficient to control worker exposure to airborne
Environmental exposure		process equipment should be checked to ensure of environmental protection legislation. In some

controis	they comply with the requirements of environmental protection registration. In some
	cases, fume scrubbers, filters or engineering modifications to the process equipment
	will be necessary to reduce emissions to acceptable levels.

Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): Recommended: Viton® fluor rubber / Short term exposure < 15 min Nitrile gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor filter (Type A)

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	White.
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point	:	Not applicable.
Boiling point	:	Not available.
Flash point	:	Closed cup: >100°C (>212°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	1	Not available.
Vapor pressure	:	Not applicable.
Vapor density	:	>1 [Air = 1]
Relative density	:	~ 1.2
Solubility	1	Not available.
Solubility in water	1	Not available.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not applicable.
Viscosity	:	refer to technical data sheet

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity					
Product/ingredient name	Result	Species	Dose	Exposure	
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	LD50 Dermal	Rat	>2000 mg/kg	-	
5	LD50 Oral	Rat	>2000 mg/kg	-	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Eyes - Mild irritant	Rabbit	-	100 mg	-
с ,	Skin - Moderate irritant	Rabbit	-	24 hours 500 uL	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	skin	Mouse	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

US

Section 11. Toxicological information

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.

Section 11. Toxicological information

Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
Peaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	EC50 9.4 mg/l	Algae - Selenastrum capricornutum	72 hours
C <i>i</i>	EC50 2.7 mg/l LC50 1.5 mg/l NOEC 0.3 mg/l	Daphnia - Daphnia magna Fish - Onchorhynchus mykiss Daphnia	48 hours 96 hours 21 days

Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	OECD 301F	5 % - Not readily - 2	8 days	20 mg/l	-
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Fresh water 4.83 days, pH 4, 25°C Fresh water 7.1 days, pH 9, 25°C Fresh water 3.58 days, pH 7, 25°C		-		Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.64 to 3.78 2.7	31 -	low low

Mobility in soil

Soil/water partition : Not a coefficient (Koc)

Other adverse effects

: Not available.

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT	TDG	Mexico	ADR/RID	IMDG	ΙΑΤΑ
	Classification	Classification	Classification	ADIVINID	INDO	
UN number	UN3082	UN3082	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	SUBSTANCIA LIQUIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N. E.P. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)
Transport hazard class(es)	9 ••••••••••••••••••••••••••••••••••••	9 • • • • •	9 • • • •	9 • • • •	9 • • • •	9 • • • •
Packing group	Ш	Ш	Ш	Ш	Ш	Ш
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes.	Yes.

Additional information

DOT Classification

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

US

Section 14. Transport information

•	
TDG Classification	 Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail. <u>Explosive Limit and Limited Quantity Index</u> 5 <u>Special provisions</u> 16, 99
Mexico Classification	 The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Special provisions 274, 331, 335
ADR/RID	 This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <u>Hazard identification number</u> 90 <u>Limited quantity</u> 5 L <u>Special provisions</u> 274, 335, 601, 375
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F Special provisions 274, 335, 969
ΙΑΤΑ	 This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. <u>Quantity limitation</u> Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964. <u>Special provisions</u> A97, A158, A197
Special precautions for user	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	: Not available.

Section 15. Regulatory information

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed
<u>SARA 302/304</u>		
Composition/information	<u>on</u> i	ingredients
No products were found.		
SARA 304 RQ	:	Not applicable.
<u>SARA 311/312</u>		

Section 15. Regulatory information

Classification

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

Composition/information on ingredients

Name	%	Classification
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	25 - 75	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	10 - 25	SKIN SENSITIZATION - Category 2 SKIN SENSITIZATION - Category 1
Phenol, polymer with formaldehyde, glycidyl ether	10 - 25	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
titanium dioxide, nanoparticle	< 1	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

State regulations

Massachusetts	;	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	None of the components are listed.
Pennsylvania	;	None of the components are listed.

California Prop. 65

WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

•	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Inventory list

United States inventory : All components are listed or exempted. (TSCA 8b)

:2021-09-30.

US

Section 15. Regulatory information

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
EYE IRRITATION - Category 2A	Calculation method Calculation method Calculation method

<u>History</u>	
Date of printing	: 2021-10-01.
Date of issue/Date of revision	: 2021-10-01.
Date of previous issue	: 2021-09-30.
Version	: 1.07
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: Not available.

References

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.